

Höhe H/mm	Breite B/mm	Wärmeleistung in Watt bei 20 °C Raumtemperatur			Höhe H/mm	Breite B/mm	Wärmeleistung in Watt bei 20 °C Raumtemperatur		
		90°/70°	75°/65°	55°/45°			90°/70°	75°/65°	55°/45°
600	210	373	296	151	1600	420	1630	1293	661
600	280	497	394	201	1600	490	1902	1508	771
600	350	622	493	252	1600	560	2174	1724	881
600	420	745	591	302	1600	630	2445	1939	991
600	490	870	690	353	1600	700	2717	2155	1101
600	560	994	788	403	1800	210	897	711	363
600	630	1119	887	453	1800	280	1197	949	485
600	700	1243	986	504	1800	350	1496	1186	606
800	210	464	368	188	1800	420	1794	1423	727
800	280	619	491	251	1800	490	2093	1660	848
800	350	774	614	314	1800	560	2392	1897	969
800	420	929	737	377	1800	630	2691	2134	1090
800	490	1083	859	439	1800	700	2991	2372	1212
800	560	1238	982	502	2000	210	973	772	394
800	630	1393	1105	565	2000	280	1299	1030	526
800	700	1549	1228	628	2000	350	1623	1287	658
1000	210	565	448	229	2000	420	1947	1544	789
1000	280	754	598	306	2000	490	2272	1802	921
1000	350	942	747	382	2000	560	2596	2059	1052
1000	420	1130	896	458	2000	630	2922	2317	1184
1000	490	1319	1046	535	2000	700	3246	2574	1315
1000	560	1507	1195	611	2200	210	1049	832	425
1000	630	1695	1344	687	2200	280	1400	1110	567
1000	700	1884	1494	763	2200	350	1749	1387	709
1200	210	665	527	269	2200	420	2100	1665	851
1200	280	886	703	359	2200	490	2449	1942	992
1200	350	1108	879	449	2200	560	2799	2220	1134
1200	420	1329	1054	539	2200	630	3149	2497	1276
1200	490	1551	1230	629	2200	700	3499	2775	1418
1200	560	1773	1406	718					
1200	630	1994	1581	808					
1200	700	2216	1757	898					
1400	210	755	599	306					
1400	280	1008	799	408					
1400	350	1260	999	510					
1400	420	1512	1199	613					
1400	490	1763	1398	714					
1400	560	2015	1598	817					
1400	630	2267	1798	919					
1400	700	2519	1998	1021					
1600	210	815	646	330					
1600	280	1087	862	440					
1600	350	1358	1077	550					

Technische Änderungen vorbehalten